



# 1915L 19-inch LCD

Touchscreen Monitor



Integrated Touch



Commercial Grade



3-Year Warranty

## Product Overview

The Elo 1915L standard format touchscreen monitor is built to withstand the rigors of continuous public use with a rugged built-for-touch design. Its stylish, thin and modern look, coupled with a retail-focused feature set and is an attractive solution for commercial touchscreen monitor needs. The 1915L can be used in a wide variety of environments with its ability to register inputs from a finger, gloved hand or soft stylus with a fast and accurate response. The touchmonitor is available with Elo's industry-leading touch technologies and multiple mounting options to support most application uses.

The Elo 1915L offers multiple mounting options to ensure installation flexibility including: wall- and pole-mount via standard VESA mount patterns as well as tabletop accommodations with the use of the desktop stand. Capped through-mount holes on the base of the touchmonitor ensure table-top security.

Available with IntelliTouch® surface acoustic wave (SAW) or AccuTouch® five-wire resistive touch technologies, both with a dual serial/ USB touch interface.

Sealed touchscreen against dirt, dust and liquid

Controls on the side rather than the front, plus lockout function for public use

## 1915L 19-inch Touchscreen Monitor

Specifications	
Model	1915L
Color	Dark gray
Active Display Area	14.82" x 11.85" (376.32mm x 301.06mm)
Dimensions* (W x D x H)	16.9" x 14.92" x 8.15" (429mm x 379mm x 207mm)
LCD Technology	Active matrix TFT LCD
Diagonal Size	19"
Aspect Ratio	5:4
Native Resolution	1280 x 1024
Other supported resolutions	1280 x 1024 at 60 or 75 Hz; 1152 x 864 at 75 Hz; 1024 x 768 at 60, 65, 70, or 75 Hz; 832 x 624 at 75 Hz (Mac); 800 x 600 at 56, 60, 72, or 75 Hz; 720 x 400 at 70 Hz; 720 x 350 at 70 Hz; 640 x 480 at 60, 66, 72, or 75 Hz
Number Of Colors	16.7 million
Brightness (Typical)	LCD panel: 250 nits; with AccuTouch: 187 nits; with IntelliTouch: 225 nits
Response Time (Tr + Tf) (Typical)	5 msec
Viewing Angle (Typical)	Horizontal: ±80° or 160° total; Vertical: ±80° or 160° total
Contrast Ratio (Typical)	1000:1
Input video format	Analog VGA
Input video signal connector	Mini D-Sub 15-Pin VGA type
Input frequency	Horizontal: 31.5-80 kHz; Vertical: 56.3-75 Hz
Power	Type: Internal, with jack to accept power from optional external brick; AC input (line) voltage: 85-265 VAC, 47-63 Hz DC input (line) voltage: 12.0 VDC ±0.75V
Power consumption	23 W
Temperature	Operating 0°C to 40°C; Storage -20°C to 60°C
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-90%
Weight (approx.)	Actual: 17.42 lbs (7.90 kg); Shipping: 25.76 lbs (11.68 kg)
Warranty	3 years
MTBF	50,000 hours demonstrated
Agency approvals	North America/Worldwide: UL/cUL, MPR II, CE, FCC, VCCI, C-tick Class B; Asia Models: BSMI, CCC, MIC, China RoHS
On-Screen Display (OSD) controls	OSD buttons: menu, up, down, select, power; OSD: contrast, brightness, H/V position, RGB (color temp), clock, phase, sharpness, recall, language (English, German, Spanish, Japanese, French); OSD disable/enable: power, OSD menu
Mounting options	Threaded-through mounting holes, under base; Removable base; 100 mm VESA mount
Other features	Security lock receptacle

## Ordering Information

Model	Part Number	Technology	Surface Treatment	Interface	Color	Availability
1915L	E607608	AccuTouch	Antiglare	Serial/USB	Dark Gray	Americas, EMEA
	E266835	IntelliTouch	Antiglare	Serial/USB	Dark Gray	Americas, EMEA
	E142981	AccuTouch	Antiglare	Serial/USB	Dark Gray	Asia/Pacific
	E966732	IntelliTouch	Antiglare	Serial/USB	Dark Gray	Asia/Pacific

To find out more about our extensive range of Elo touch solutions, go to [elotouch.eu](http://elotouch.eu), or call the office nearest you.

### North America

Tel +1 408 597 8000  
 Fax +1 408 597 8050  
[elosales.na@elotouch.com](mailto:elosales.na@elotouch.com)

### Europe

Tel +32 (0)16 70 45 00  
 Fax +32 (0)16 70 45 49  
[elosales@elotouch.com](mailto:elosales@elotouch.com)

### Asia-Pacific

Tel +86 (21) 3329 1385  
 Fax +86 (21) 3329 1400  
[www.elotouch.com.cn](http://www.elotouch.com.cn)

### Latin America

Tel +1 786-923-0251  
 Fax +1 305-931-0124  
[elosales.latam@elotouch.com](mailto:elosales.latam@elotouch.com)

Elo Touch Solutions, Inc. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo (logo) and Elo Touch Solutions are trademarks of Elo Touch Solutions, Inc. © 2017 Elo Touch Solutions, Inc. All rights reserved. 17061AES00069

