



I-Series for Windows

All-in-One Touchscreen Signage



Integrated Touch



Commercial Grade



3-Year Warranty

Product Overview

The Elo I-Series for Windows AiO interactive signage delivers commercial-grade computing with the capabilities, security and enterprise infrastructure of a powerful Windows-based platform with a sleek, ultra-thin, yet ruggedized form factor down to 1.5 inches thin. Available in two wide format display sizes - 15.6" and 21.5", both I-Series for Windows AiO touchscreens feature our industry-leading TouchPro® PCAP technology that provide a 10-touch tablet-like interactive experience. With edge-to-edge glass, it is easy to clean with no edges to trap dirt and grease, the I-Series can be flexibly mounted anywhere in portrait, landscape or table-top orientation using Elo wall, floor and tabletop mounting accessories making application use endless.

The 6th generation Intel Skylake i5 with HD530 graphics for top end performance or the fan-less Braswell Celeron ideal for ultra-low noise environments. Both models are available pre-installed with Windows 10, Windows 7 or No OS configurations (Windows 8.1 is available upon request).

Available in 15.6" and 21.5" sizes with high-performance computing and graphics, integrated display, and Elo's TouchPro® PCAP (10 Touch) technology

Universal snap-in peripherals NFC/RFID reader, barcode reader, MSR, and mounting options (poles, shelf & floor stands, shelf & wall mounts)

Wifi and Bluetooth 4.0

I-Series for Windows AiO Touchscreen Signage

Model	ESYxxi2	ESYxxi5
Processor	Intel Celeron N3160 Quad-Core Processor 1.6 GHz (up to 2.24 GHz) 2MB L2 Cache	Intel i5-6500TE Quad-Core Processor 2.3GHz (up to 3.3 GHz) 6MB Smart Cache
Graphics	Intel HD Graphics 400	Intel HD Graphics 530
BIOS	AMI	
Memory (RAM)	2GB DDR3L SODIMM on 1 of 2 slot (Expandable to 8GB maximum)	4GB DDR4 SODIMM on 1 of 2 slot (Expandable to 16GB maximum)
Storage	128GB 2.5" 7mm SATA SSD 72 TBW	
USB Ports	2 x USB 3.0; 3 x Micro USB for Elo peripherals	4 x USB 3.0 ; 3 x Micro USB for Elo peripherals
Ethernet Port	1 x LAN RJ45 (Gigabit)	
Wireless Connectivity	Wi-Fi 802.11 a/b/g/n/ac and Bluetooth 4.0	
Additional Video Out	2nd Micro HDMI out	
Audio Port	1 x 3.5mm line out	
Webcam	Max resolution: 1920 x 1080 30fps (MJPEG), Auto Focus @ 10cm ~ Infinity, Automatic Exposure Control, Automatic White Balance Control, Automatic Gain Control	
Display	15.6" diagonal, active matrix TFT LED LCD; 21.5" diagonal, active matrix TFT LED LCD	
On-Screen Display (OSD)	Power, Brightness Up, Brightness Down, Volume Up, Volume Down	
Aspect Ratio	16:9 (widescreen)	
Active Display Area (W x H)	15.6": 13.6" x 7.6" (344.2mm x 193.5mm); 21.5": 18.6" x 10.5" (476mm x 267.8mm)	
Native (optimal) Resolution	1920 x 1080 @ 60Hz	
Colors	15.6": 262K (6 bit); 21.5": 16.7M (8 bit)	
Brightness (typical)	15.6" LCD panel: 300 nits, TouchPro (PCAP): 270 nits; 21.5" LCD panel: 250 nits, TouchPro (PCAP): 225 nits	
Response Time Total (typical)	15.6" LCD panel: 25ms; 21.5" LCD panel: 30ms	
Viewing Angle (typical)	15.6" LCD panel: Horizontal: 85°/170° total, Vertical: 85°/170° total 21.5" LCD panel: Horizontal: 89°/178° total, Vertical: 89°/178° total	
Contrast Ratio (typical)	15.6" LCD panel: 700:1; 21.5" LCD panel: 3000:1	
Touch Technologies	Elo TouchPro (PCAP)	
Power	External 19VDC universal-type power supply brick, AC input voltage: 100-240 VAC, Input frequency: 50-60 Hz 15.6" with i2: Maximum output power: 65W (Max Draw: 74W); 21.5" with i2 and 15.6" with i5: Maximum output power: 90W (Max Draw: 100W); 21.5" with i5: Maximum output power: 150W (Max Draw: 170W)	
Max Power Consumption (without peripherals)	15.6" with i2: 33.97W; 21.5" with i2: 43.97W; 15.6" with i5: 80.63W; 21.5" with i5: 90.63W	
Maximum Touchcomputer Dimensions (W x H x D)	15.6": 15.2" x 9.8" x 1.5" (387mm x 249mm x 39mm); 21.5": 20.6" x 12.76" x 1.8" (524mm x 324mm x 45mm)	
Shipping Box Dimensions (W x H x D)	15.6": 19.29" x 14.96" x 5.51" (490mm x 380mm x 140mm); 21.5": 26.97" x 19.41" x 7.09" (685mm x 493mm x 180mm)	
Weight	Unpacked: 15.6": 5.64 lbs (2.56 kg); 21.5": 12.05 lbs (5.47 kg) Packaged: 15.6": 9.71 lbs (4.41 kg); 21.5": 17.65 lbs (8.03 kg)	
Temperature	Operating: 0°C to 35°C / 32°F to 95°F; Storage: -20°C to 60°C / -4°F to 140°F	
Humidity (non-condensing)	Operating: 20% to 80%; Storage: 5% to 95%	
Regulatory approvals and declarations	UL/cUL, FCC, TUV, CB, CE, VCCI	
Mounting Options	Wall/pole mount or secure base to tabletop/desktop	
Enclosure Color	Black	
Real-Time Clock	Replaceable lithium-ion battery for clock	
Sealing	Touchscreen sealed to sub-bezel / Touchscreen sealed to LCD	
Warranty	3-year warranty extendable up to 5 years.	
MTBF	50,000 hours demonstrated	
What's in the box	I-Series Windows Touchcomputer, North America Power Cable, European Power Cable, Power Adapter, QIG	

Ordering Information

Model	Part Number	Processor	OS
i-Series for Windows 15-inch	E222775	Intel Celeron	No OS
	E222776	Intel Celeron	Windows 7
	E970376	Intel Celeron	Windows 10
	E222781	Intel i5	No OS
	E222782	Intel i5	Windows 7
	E970665	Intel i5	Windows 10
Model	Part Number	Processor	OS
i-Series for Windows 22-inch	E222787	Intel Celeron	No OS
	E222788	Intel Celeron	Windows 7
	E970879	Intel Celeron	Windows 10
	E222793	Intel i5	No OS
	E222794	Intel i5	Windows 7
	E971081	Intel i5	Windows 10

To find out more about our extensive range of Elo touch solutions, go to elotouch.com, or call the office nearest you.

North America

Tel +1 408 597 8000
Fax +1 408 597 8050
customerservice@elotouch.com

Europe

Tel +32 (0)16 70 45 00
Fax +32 (0)16 70 45 49
EMEA.Sales@elotouch.com

Asia-Pacific

Tel +86 (21) 3329 1385
Fax +86 (21) 3329 1400
www.elotouch.com.cn

Latin America

Tel +52 55 2281-6958
elosales.latam@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo and EloView are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2018 Elo Touch Solutions, Inc. All rights reserved. 18102AE500011

