

# FlexiOutdoor Access Gate

## OUTDOOR KIOSK



### TECHNICAL DATA

#### STRUCTURE

Powder-coated aluminum profiles

#### MONITOR

Litemax  
19" / 22"  
1600 nits

#### TOUCHSCREEN

Zytronic anti-glare glass  
Projected capacitive touch

#### CONTROLLER

Automatic temperature management  
Emergency shutdown/startup  
Unit surveillance  
Noise-cancelling fan system

#### PROTECTION & RESISTANCE

IP65 rating  
Triple layer sealing  
Removable dust filter  
Standard heating unit 450W  
4 ventilation fans  
-20 to 40 degrees celcius

#### SECURITY

Dirak triple-point key locking system

#### MOUNTING

Concrete foundation

#### ACCESS

Front opening

#### RECOMMENDED MAX PC SIZE

Width: 200mm  
Height: 200mm  
Depth: 100mm

#### WEIGHT

Approximately 150 kg

#### FOOTSTAND

Powder-coated aluminum



### OPTIONS

#### BRANDING

Graphic laminate  
Special RAL colors

#### HARDWARE

Payment interface  
Card reader  
Scanner QR - 2D - 1D  
RFID scanner  
Receipt printer  
A4 printer  
Intercom VOIP  
Speakers  
Camera  
Keyboard  
LED lighting  
Antenna

#### ADDITIONAL WEATHER RESISTANCE

Aircondition unit  
(Above 40 degrees Celcius)  
Heating unit 850W  
(Below -20 degrees Celcius)

#### ACCESS

Rear opening

### ROSENDAHL CONCEPTKIOSK A/S

+45 76 72 02 60

info@conceptkiosk.com

www.conceptkiosk.com

Thorsvej 233 • 7200 Grindsted • Denmark

facebook.com/conceptkiosk

linkedin.com/company/conceptkiosk