

FlexiOutdoor Wall

OUTDOOR KIOSK



TECHNICAL DATA

STRUCTURE

Powder-coated aluminum profiles

MONITOR

Litemax
19" / 22"
1600 nits

TOUCHSCREEN

Zytronic anti-glare glass
Projected capacitive touch

CONTROLLER

Automatic temperature management
Emergency shutdown/startup
Unit surveillance
Noise-cancelling fan system

PROTECTION & RESISTANCE

IP65 rating
Triple-layer sealing
Removable dust filter
Standard heating unit 450W
4 ventilation fans
-20 to 40 degrees Celcius

SECURITY

Dirak triple-point key locking system

MOUNTING

Wall-hanging

ACCESS

Front opening

RECOMMENDED MAX PC SIZE

Width: 200mm
Height: 200mm
Depth: 100mm

WEIGHT

Approximately 85 kg

FOOTSTAND

Powder-coated aluminum



OPTIONS

BRANDING

Graphic laminate
Special RAL colors

HARDWARE

Payment interface
Card reader
Scanner QR - 2D - 1D
RFID scanner
Receipt printer
A4 printer
Intercom VOIP
Speakers
Camera
Keyboard
LED lighting
Antenna

ADDITIONAL WEATHER RESISTANCE

Aircondition unit
(Above 40 degrees Celcius)
Heating unit 850W
(Below -20 degrees Celcius)

ACCESS

Rear opening

ROSENDAHL CONCEPTKIOSK A/S

+45 76 72 02 60

info@conceptkiosk.com

www.conceptkiosk.com

Thorsvej 233 • 7200 Grindsted • Denmark

facebook.com/conceptkiosk

linkedin.com/company/conceptkiosk