

Smartphone

Smart-Ex® 203

SMART-EX203-*

- Android[™] 14
- Wireless connections such as 5G NR, WWAN, Wi-Fi and Bluetooth®
- NFC technology for wireless applications
- Dual SIM (eSIM + nano-SIM)









Technical Data

Hardware	
Processor	Qualcomm QCM4490 3GPP Rel 16 support
RAM	8 GByte
Camera	Version without camera available.
Front camera	16 MP
Main camera	48 MP with autofocus and LED flash
Scanner	Optional additional 1D/2D-scan module SM-Ex S203 SR (#70192137, Zebra SE4107) available as accessory
Internal data memory	128 GByte
Optional data memory	microSD card up to 512 GByte
Sensors	Biometric, Accelerometer, Gyrometer, Magnetometer, Barometer, Proximity, Ambient light
Indicators/operating means	
Display	
Touch screen technology	Capacitive multitouch
Panel type	TFT
Screen size	16 cm / 6.3 inch
Resolution	1080 x 2340 (FHD+)
Special Features	Can be operated while wearing gloves Use in rain and wet conditions
Key	Programmable push-to-talk and multifunction button (can be used as an alarm button) Power button Volume up/down
Electrical specifications	
Battery type	Li-ion 3.8 V 4500 mAh 17.1 Wh
Interface	
I/O ports	USB-C additional interface for peripherals Charging pads for charging in docking station
Communication	
Mobile standard	
4G	LTE-FDD: B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B18, B19, B20, B25, B26, B28, B29, B30, B66, B71 LTE-TDD: B34, B38, B39, B40, B41, B42, B43, B48

5G

 $n1,\,n2,\,n3,\,n5,\,n7,\,n8,\,n12,\,n13,\,n14,\,n18,\,n20,\,n25,\,n28,\,n29,\,n30,\,n38,\,n40,\,n41,\,n48,\,n66,\,n71,\,n77,\,n78,\,n79$

Technical Data

WLAN IEEE 802.11 2.4 GHz - b/g/n 5 GHz / 6 GHz: - a/ac/ax (Wi-Fi 6e) Bluetooth 5.2 (BLE supported) GPS sensor GPS, GLONASS, Galileo, QZSS, BeiDou NFC SIM card Dual SIM (eSIM + nano-SIM) Software Android™ 14 with GMS (Google Mobile Services) Operating system Android™ Enterprise Recommended verified device (pending) ARCore certification (pending) Cybersecurity IT security **Biometrics** Fingerprint sensor (side) Updates Security updates until 2032 Operating system updates up to Android™ 18 **Ambient conditions** Ambient temperature -20 ... 55 °C (-4 ... 131 °F) -20 ... 55 °C (-4 ... 131 °F) Storage temperature Mechanical specifications IP68 according to EN/IEC 60529 MIL-STD-810H Degree of protection 365 g Mass **Dimensions** $W \times H \times D$ 86 mm x 177 mm x 17 mm Data for application in connection with hazardous areas ATEX approval ATEX certificate Pending Ex ic IIC T4 Gc Ex ic IIIC T135°C Dc T_{amb}= -20 °C ... +55 °C ATEX marking International approvals IECEx approval IECEx certificate Pending Ex ic IIC T4 Gc Ex ic IIIC T135°C Dc T_{amb}= -20 °C ... +55 °C IECEx marking NEC/CEC approval **NEC/CEC** certificate Pending Class I, Division 2, Groups A - D T4 Class II, Division 2, Groups F,G T4 **NEC/CEC** marking T_{amb}= -20 °C ... +55 °C **General information** Note Android is a trademark of Google LLC. Scope of delivery Smart-Ex® 203 Li-Ion battery Charger USB cable Torx T8 Documentation

Accessories

Accessories for this product can be found on the internet at www.pepperl-fuchs.com.

